



Neutral UV-Oil 2306

Water-based UV-oil that maintains the unfinished look

Technical Data Sheet

29.01.2022 - p. 1/2

Neutral UV-Oil 2306 is a unique water-based UV-oil that provides the wood with a durable protection as well as maintains the untreated look of the wood. Using this oil ensures fast production speeds.

- **Untreated appearance of the wood (invisible look)**
- **Ensures UV-oiled floors**
- **Fast production speeds**



Application area

For a neutral surface treatment of wooden floors and parquets in hardwood and softwood.

Work description

Treatment	0
Please note	Viscosity correction: The product can be diluted with a maximum of 5 % water.

Drying time

Drying time	Flash off: Water must be removed before exposing to UV-drying. First coat: Drying tunnel with max. 40°C and good air circulation, or room temperature min. 3 minutes. Drying: UV-drying with Hg lamps, min. 400-600 mJ/cm ² for each lamp. Production speed 10 m/min.
Fully hard	Immediately after UV-drying



Neutral UV-Oil 2306

Water-based UV-oil that maintains the unfinished look

Technical Data Sheet

29.01.2022 - p. 2/2

Technical data

Density	1.00-1.10 g/ml.
Solid content	30-40%
Shelf life	2 years
Viscosity	50-55 Sec. DIN Cup 4
Coverage	30-40 m ² /L
Colours	Invisible look, white appearance in pail.
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	110 g/L
Packaging	10 liters

Maintenance and related products

Weekly cleaning	WOCA Natural Soap
Monthly care	WOCA Invisible Oil care
Related products	Re-oiling: WOCA Invisible Oil care

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.