



Pre-Color
Water-based stain for interior wood

Technical_Data_Sheet_Label
29.01.2022 - p. 1/2

Pre-Color is a water-based stain for unfinished and sanded interior wood surfaces, such as floors, stairs, furniture and panels. The stain colors the wood and enhances the natural wood grain.

- **Emphasizes the natural grain for a more attractive look**
- **Gives the wood a beautiful, colored surface**
- **Can be used with all WOCA oils**



AppArea

For staining untreated, new, or newly sanded wooden surfaces. Ideal for all types of wood.

Work_Descrip_Label

Preparation_Label	<p>Product, room and floor temperature must be between 59-77°F. Wood moisture content must not exceed 12%. Ensure good ventilation during application and when drying. The wood must be newly sanded, use grit 100-120 for the final sanding. Vacuum thoroughly. Clean the wood with WOCA Intensive Wood Cleaner and leave it to dry for at least 8 hours before applying the stain.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
FinalSanding	g100til120
Treatment	<p>Thoroughly shake the container of PreColor, both before and during use. Containers with different batch numbers should be mixed to avoid color mismatch. Apply an even coat of undiluted stain along the wood grain with WOCA Applicator. Use at least 1 L of Pre-Color per 100 sq.ft. On vertical wood, apply from top to bottom. Leave the surface to dry for 8-12 hours. Sand with a green pad to obtain a smooth surface and vacuum thoroughly. The surface must be finished using one of WOCA's oils, following the product instructions.</p>
NoteTxt	<p>The surface must be finished using one of WOCA's oils, following the product instructions. Pre-Colour cannot be used alone as it only provides colour to the wood, and not protection.</p>

DryingTime

DryingTime	6-12 hours at 68°F
------------	--------------------



Pre-Color

Water-based stain for interior wood

Technical_Data_Sheet_Label

29.01.2022 - p. 2/2

Techdata_label

Declaration	Water, pigments.
Density	0.95-1.00 g/ml.
ShelfLife	3 years
AppTemp	+59-77°F and approx. 50% air humidity.
Consumption	85-110 sq.ft./L
Colours	White, Grey
CleaningTools	Use water
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	Max: 165 g/l.
AvailPotSizes	2.5

MaintenanceProd

BasicOilingProd	Master Colour Oil Diamond Oil Active
RelatedProducts	Intensive Wood Cleaner, #551525US

Contact_Label

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.