

Reactive Stain

For pre-colouring of tannin-rich wood

Technical Data Sheet 29.01.2022 - p. 1/2

Reactive Stain is a water-based stain specially formulated to create an aged and rustic look on tannin-rich wood in a fast and simple way. It reacts quickly after the application and provides a vibrant and distinctive colour, depending on the type of wood used. Modern and unique colour solutions can be achieved in combination with WOCA air-drying and UV-drying oils.



- Unique look
- Quick colour reaction
- The final colour depends on the tannin content in the wood
- Must be treated afterwards with WOCA oils

Application area

For colour treatment of tannin-rich wooden floors, furniture and wall panels.

Work description

Treatment 0

Please note Can be diluted with water to obtain the desired colour strength. Full colour development within 24

hours.

Drying time

Drying time Drying on racks or pallets. Drying is accelerated in drying tunnel with max. 40°C and good air

circulation.

Fully hard 3 days at 20°C



Technical data

Density 1.00-1.10 g/ml.

pH-value pH 8-9 Solid content 10-20%

Shelf life 3 years

Viscosity 10-15 Sec. DIN Cup 4

Colours Trendy colours from dark grey to dark brown.

Storage +10-25°C. Keep out of reach of children. Do not expose to

heat (e.g. sunlight). Store frost-free during winter and cool

during summer.

VOC 70 g/L

Packaging 10 L container.

Maintenance and related products

Weekly cleaning Depends on the finishing oil

Monthly care Depends on the finishing oil

Contact

WOCA Denmark A/S

Tværvej 6

DK - 6640 Lunderskov T +45 9958 5600

info@wocadenmark.com wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.