

Pre-Colour is a water-based stain for unfinished and sanded interior wood surfaces, such as floors, stairs, furniture and panels. The stain colours the wood and enhances the natural wood grain.

- **Emphasizes the natural grain for a more attractive look**
- **Gives the wood a beautiful, coloured surface**
- **Can be used with all WOCA oils**



Application area

For staining untreated, new, or newly sanded wooden surfaces. Ideal for all types of wood.

Work description

Preparation	<p>Product, room and floor temperature must be between 15-25°C. Wood humidity must not exceed 12%. Ensure good ventilation during application and when drying. The wood must be newly sanded, use grit 100-120 for the final sanding. Vacuum thoroughly. Clean the wood with WOCA Intensive Wood Cleaner and leave it to dry for at least 8 hours before applying the stain.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Final sanding	Grit 100-120.
Treatment	<p>Thoroughly shake the container of Pre-Colour, both before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply an even coat of undiluted stain along the wood grain with WOCA Applicator. A more uniform colour is obtained if the wet stain is polished into the wood using a polishing machine and a beige pad. Use at least 1 L of Pre-Colour per 10 m². On vertically mounted wood, apply from top to bottom. Leave the surface to dry for 8-12 hours. Sand with a green pad to obtain a smooth surface and vacuum thoroughly.</p>
Please note	<p>The surface must be finished using one of WOCA's oils, following the product instructions. Pre-Colour cannot be used alone as it only provides colour to the wood, and not protection.</p>

Drying time

Drying time	6-12 hours at 20°C
-------------	--------------------



Pre-Colour

Water-based stain for interior wood

Technical Data Sheet

29.01.2022 - p. 2/2

Technical data

Density	1.10-1.20 g/ml.
Shelf life	3 years
Application Temperature	+15-25°C and approx. 50% air humidity.
Coverage	8-10 m ² /L
Colours	White, Grey, Black, Brown
Cleaning of tools	Use water
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	This product contains a maximum of 100 g VOC/L. The limit value is 100 g VOC/L (cat. A/k).
Packaging	2.5 liters

Maintenance and related products

Basic oiling	Master Colour Oil, #522072AA Diamond Oil Active, #565010A
Related products	Intensive Wood Cleaner, #551525A

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.