



Tropical Filler

For filling gaps, knots and cracks in wood manually

Technical Data Sheet

29.01.2022 - p. 1/2

Tropical Filler is a high-quality environmentally-friendly powder-based filler that is easy to mix. It has the same qualities as the old WOCA Wood Filler, however the Tropical Filler is adjusted to fit the tropical climate (high humidity areas i.e. 80 %), but can also be used in areas with lower humidity. It is suitable for various types of repairs in wood and is applicable for wood repairs with a depth up to 15 mm. You can mix and match the different colours as you wish, but it is also possible to add colour pigment or stain to the mixture to obtain a customized colour. There is no expiration date on the raw powder if it is properly protected from moisture, water and foreign objects.

- **Can be surface treated with both stain, lacquer, UV- and oxidizing oil**
- **Offers a countless number of colour options**
- **Made of natural raw materials**



Application area

For use on furniture and floorings. Suitable for all types of wood, solid as well as veneered surfaces. Only for indoor use.

Work description

Treatment	0
Please note	Viscosity Correction: A small amount of water may be added to the mixture within the first 5 minutes, if needed.

Drying time

Fully hard	30-60 minutes at 20°C
------------	-----------------------



Tropical Filler

For filling gaps, knots and cracks in wood manually

Technical Data Sheet

29.01.2022 - p. 2/2

Technical data

Density	0.95-1.00 g/ml.
pH-value	pH 7-8
Solid content	95-100%
Shelf life	3 years
Colours	Smoked oak
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
Packaging	20 liters

Maintenance and related products

Weekly cleaning	Depends on the finishing oil.
Monthly care	Depends on the finishing oil.
Related products	Stain, oil or lacquer

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.