

Panel White is a water-based product for the lightening up of yellowed wood, e.g. ceilings and wall panels. Panel White is used indoors for untreated and lacquered softwood.



- **Preserves the natural structure of the wood**
- **Delays discolourating of resin and protects against “popping” of the knots**
- **Certified by IBR**

Application area

For lightening of any type of unfinished or lacquered panels, doors and door frames made in light coloured types of wood. Not suitable for wood floors.

Work description

Preparation	<p>The wood must be clean and completely dry. Wash with Intensive Wood Cleaner mixed with water in the ratio 1:40. Wipe off with clean water. Loose lacquer remains of earlier lacquered surfaces must be removed.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Stir the Panel White carefully before and during use. Buckets with different batch numbers should be mixed before use to avoid differences in shade and gloss. Apply the product with a brush in an even layer lengthwise the wood grain. Do not apply on more than 3-4 boards at the time and finish them to avoid overlaps.</p>

Drying time

Drying time before second treatment	Approx. 4 hours.
Drying time	Approx. 2 hours.



Technical data

Declaration	Water, alkyd dispersion, pigments.
Density	1.26-1.34
pH-value	Approx. 7-8
Shelf life	36M
Coverage	10-12 m ² /L, depending on wood type and surface.
Colours	White and Extra White
Cleaning of tools	Water and soap.
VOC	This product contains a maximum of 60 g VOC/L. The limit value is 130 g VOC/L [cat. A/e].
Packaging	2.5 L
Authorisations	IBR-certified

Maintenance and related products

Related products	Intensive Wood Cleaner, #551525A
Application tools	Wide brush for lye or water-based products. Small round brush for profiles and edges.

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.