



Wood Floor Paint is a unique product providing a rich built-up surface. The product is suitable for all types of woodwork, such as floors and staircases. The unique water-based polyurethane modified acrylic paint system provides a fast-drying and hardwearing surface which is easy to clean and maintain. Wood Floor Paint is an environmentally friendly product to work with. It is NMP-free and has low VOC content.

- **Full covering**
- **Low VOC**
- **Strong and resistant**
- **Hardwearing**
- **Easy aftercare**



Application area

Suitable for all types of solid woodwork, such as floors and staircases.

Work description

Preparation	<p>The surface must be completely clean, dry, and free from resin, grease, oil, wax, lime, as well as cleaning residues. Use WOCA Intensive Wood Cleaner for thorough cleaning. Sanding: - Of new surfaces: Sand with sanding paper grit 100-120. Remove sanding dust from surface with vacuum cleaner before applying the Wood Floor Paint. - Of old surfaces: Old surfaces with old paint/lacquers severely damaged etc. must be leveled and sanded to bare wood. Final sanding with grit 100-120. Remove sanding dust from surface with vacuum cleaner before applying the Wood Floor Paint.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Stir the paint carefully before and during use. Container with different batch numbers should be mixed before use to avoid differences in shade and gloss. Apply a uniform coat of Wood Floor Paint using a brush or a short haired paint roller (hair length 3mm). Work lengthwise of the boards. (It is recommended to dilute the first coat with water up to 20% as a primer). Leave to dry for approx. 4-6 hours at 20°C. After drying, the surface is de-nipped with a Bordeaux coloured lacquer sanding pad or fine sanding paper grit 220/240 – vacuum clean floor for dust before next step. Apply the second layer of Wood Floor Paint like the first coat and leave to dry again.</p>
Please note	<p>For commercial and heavy duty areas, it is recommended to de-nip surface again and apply a 3rd coat. WOCA Floor Paint is not recommended for use in wet rooms or outdoor areas.</p>

Drying time

Light use	24 hours at 20°C
Fully hard	7 days at 20°C



Technical data

Declaration	Polyurethane modified Acrylic, Pigments, Filler, Water.
Density	1.20-1.30 g/ml.
Shelf life	3 years
Application Temperature	+15-25°C and approx. 50% air humidity.
Coverage	6-10 m ² /L
Colours	White
Cleaning of tools	Use soap and water
Storage	+10-30°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	This product contains a maximum of 105 g VOC/L. The limit value is 130 g VOC/L [cat. A/d].

Maintenance and related products

Weekly cleaning	Master Cleaner
Half yearly care	Master Care
Related products	Intensive Wood Cleaner Wood Stain Remover

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.