



Driftwood Lye is a unique, water-based product, which gives the wood a weather-beaten patina. The product is primarily for oak wood. By using this product, the wood will get a very nice two-dimensional design. Finally, the surface must be treated with one of the WOCA oils.

- **Gives oak a weather-beaten patina**
- **Requires additional treatment with oil**
- **Water-based**
- **Only suitable for oak wood**



Application area

Used for priming of oak wood. Creates a weather-beaten patina.

Work description

Preparation	The unfinished woodwork must be clean, dry and finely sanded (grit 100-120) before applying the lye. Always remember to test on a less visible spot to check the compatibility of the surface with the product.
Treatment	Shake the container well and pour the lye into a plastic bucket. It is important that no pigments are left in the container. Stir regularly during the application to prevent the pigments from settling to the bottom. Apply an even coat of the lye with the WOCA Applicator, a nylon brush or roller lengthwise along the grain. Apply at least 1 L of lye per 10 m ² of wood. Leave wood to dry for approx. 8-12 hours at 20°C. De-nib standing fibres and remove excess pigments with a medium e.g. green or bordeaux, sanding polishing pad. Remove the sanding dust with a vacuum cleaner. Finish the wood surface with a WOCA oil.

Drying time

Drying time	8-12 hours.
-------------	-------------



Technical data

Density	1.07-1.16
pH-value	13-14
Shelf life	36M
Coverage	8-10 m ² /L, depending on wood type and surface.
Colours	White and grey
Cleaning of tools	Water.
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	This product contains max. 0 g VOC /L. The limit value is 30g VOC/L [Cat. A/g].
Packaging	2.5 L
Authorisations	IBR-certified

Maintenance and related products

Application tools	WOCA Applicator, a nylon brush or roller Plastic bucket
-------------------	--

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.