




Hardener for Fast/Tropical Fillers is designed to add strength to WOCA Fastfiller and WOCA Tropical Filler. Using this hardener shortens the overall drying time of WOCA filler repairs, increases the general resistance of the repairs and makes the fillers suitable for hard wire brushing.

- **Adds strength to fillers**
- **Prevents fillers from falling out of cracks and knots when wire brushed**



Application area

For adding strength to fillers when repairing cracks and knots in all types of wood.

Work description

Treatment 0

Drying time

Drying time Fillers mixed with hardener reduces the overall drying time with approx. 30%.



Technical data

Density	1.00-1.10 g/ml.
Solid content	95-100%
Shelf life	3 years
Colours	Colourless
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	0 g/L
Packaging	750 ml

Maintenance and related products

Weekly cleaning	Depends on the finishing oil.
Monthly care	Depends on the finishing oil.

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.