

Exterior Deep Cleaner is an intensive cleaning product, which rejuvenates patinated outdoor wood. It is a ready-mixed, thick-flowing product, which is easy to apply, even to vertical surfaces. Exterior Deep Cleaner penetrates deep into the wood and removes dirt, coatings and grey patina. For optimum protection, the wood should be treated with WOCA Exterior Wood Oil after cleaning.

- Thick viscosity
- Easy to apply
- Deep cleaning
- Non-drip
- Removal of dirt, coatings and grey patina



## Application area

---

Suitable for outdoor wooden decks, wall coverings, fences, garden furniture etc.

## Work description

---

Preparation	Cleaning should be done in dry (ideally overcast) weather, as the cleaner must not be allowed to dry out. Avoid direct sunlight and excessive heat. Clean the wood to remove leaves and algae. Soak the wood, using plenty of water. Use a garden hose if possible.  Exterior Deep Cleaner is ready-mixed and should not be diluted.
Treatment	The wood must be soaking wet before application of Exterior Deep Cleaner. Using a brush, roller or spray gun, apply Exterior Deep Cleaner as a smooth, uniform layer and allow the cleaner to work. After approximately 15-20 minutes, scrub the wood using a stiff-bristled brush. We recommend that you use WOCA silicon brush for the best results. Rinse off the Exterior Deep Cleaner, using plenty of water and a stiff-bristled brush. The wood must be left to dry for at least 48 hours, before application of WOCA Exterior Wood Oil.
Note	If a completely smooth surface is desired, de-nip the wood with a grit 180-240 sanding pad before oiling.

## Drying time

---

Drying time	48 hours at 15 -20° C
-------------	-----------------------

## Technical data

---

Declaration	Oxalic acid, < 5% cationic and non-ionic surfactants.
Density	1.02 kg/L
pH-value	<1
Shelf life	36M
Application Temperature	+ 10-25° C, ideally cloudy weather.
Coverage	Approx. 8-10 m <sup>2</sup> /L
Colours	Transparent, slight white tint
Cleaning of tools	Use water
Storage	Frost-free and away from direct sunlight.
Packaging	0.75 L

## Maintenance and related products

---

Application tools	Brush, roller or spray gun
-------------------	----------------------------

## Contact

---

WOCA Denmark A/S  
Tværvvej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.