



Use Maintenance Oil Diamond Active for the ultimate care and maintenance of your oiled wooden floor. This exclusive, low-odour, extremely tough maintenance oil is made from the absolute highest quality raw materials, to benefit both you and your oiled floor. In addition to being very easy to use and assuring minimal product waste, the maintenance oil refreshes the natural, warm glow of the wood and increases resistance to stains and wear, via a unique hyper cross linking technology. Maintenance Oil Diamond Active is suitable for both manual and machine application to oiled floors.

- **Resistant to liquids such as water, coffee, tea and red wine**
- **Resistant to scratches and marks**
- **Gives the wood a beautiful, breathable surface**
- **IBR-certified**



Application area

For oiled surfaces.

Work description

Preparation	<p>It is important that the product, the room and the floor are at a temperature between 15 °C and 30 °C and that air humidity is approx. 50 %. Wood humidity must not exceed 12 %. Make sure that the room is well-ventilated for optimal evaporation and drying time.</p> <p>The surface must be free of grime, grease and wax. Wash the floor with WOCA Intensive Wood Cleaner and leave the floor to dry for a least 8 hours or until it is completely dry.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Thoroughly shake the container of Maintenance Oil Diamond Active, both before and during use. Apply approx. 1 dl oil per 4 m² floor using a pad, short-bristled paint roller (3-4 mm) or a buffing machine with a white or beige pad on slightly larger areas. Make sure that the oil is rubbed well into the wood. Continue polishing until the wood seems saturated and the surface has an even, uniform appearance. Remove excess oil with clean, lint-free cotton cloths, before proceeding to the next section. The surface should not appear wet and no excess oil should remain on the surface. Continue, following the aforementioned method until the whole floor has been treated.</p> <p>If the floor is polished with a buffing machine, it can be used with caution after 4 hours of drying time at 20°C. If polished manually, the floor can be used with caution after approximately 24 hours.</p>
Note	<p>Do not expose the floor to water or clean it for the first 3 days, while the oil is hardening.</p>

Drying time

Drying time	24 hours at 20°C.
Drying time when machine polished	4 hours at 20° C
Drying time when hand polished	24 hours at 20° C
Fully hard	3 days at 20°C
Recommendation	Do not expose the floor to water or clean it for the first 48 hours, while the oil is hardening.



Technical data

Density	0.90 g/ml
Solid content	Approx. 70 %
Shelf life	36M
Application Temperature	+ 15-30°C
Coverage	40-50 m ² /L, depending on wood type and surface.
Colours	Natural and white
Cleaning of tools	WOCA Solvent or turpentine
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	This product contains max. 100 g VOC/l. Permitted value is 500 g VOC/l [cat.A/i].
Packaging	2.5 L and 5 L
Migration_Test	EN 71-3:2013
Authorisations	Danish Indoor Climate Labelling IBR: TVOC28/A+, AgBB Z-157.10-198

Maintenance and related products

Weekly cleaning	Natural Soap, #511010
Monthly care	Oil Refreshing Soap, #511210
Re-oiling	Diamond Oil Active, #215025
Related products	Intensive Wood Cleaner, #551525
Application tools	Paint Roller, 4 mm luv, #88004 Paint roller handle, 25mm, #599650 Telescopic rod, #599651

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.