



Invisible Oil Primer is a water-based wood primer with excellent adhesion, that gives wood a matt, untreated appearance when combined with WOCA Invisible Oil. Invisible Oil Primer is the first stage in a high quality water-based oiling system and should therefore be used together with WOCA Invisible Oil. The Invisible system has been developed for use with light wood varieties, where a high oiling quality and newly-sanded, untreated appearance are required. The range gives the floor a surface that is both comfortable to walk on and soft to the touch. The floor is also left with a soft, water-resistant surface that is easy to clean and maintain.

- **Gives the floor an untreated appearance**
- **Resistant to liquids such as water, coffee, tea and red wine**
- **Gives the wood a beautiful, breathable surface**
- **IBR-certified**



AppArea

For priming untreated, new or newly-sanded wooden surfaces in light wood varieties. Should be treated after priming with Invisible Oil.

Work_Descrip_Label

Preparation_Label It is important that the product, the room and the floor are at a temperature between 59°F and 86°F and that air humidity is approx. 50 %. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time. The wood must be newly-sanded, with grit 100-150 for the final sanding. Vacuum thoroughly. Wash the floor with WOCA Intensive Wood Cleaner and leave the floor to dry for at least 8 hours before application of the primer.

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

FinalSanding Grit 100-150

Treatment Thoroughly shake the container of primer, both before and during use. Containers with different batch numbers should be mixed to avoid color mismatch. Apply the primer using a 1/4" nap paint roller in an even coat. Work in small areas of no more than 100 sq. ft. at a time. Leave the primer to soak in for up to 5 minutes. Rub the primer into the wood until the floor appears saturated. Use a buffing machine with a red pad. Regularly change the buffing pad to prevent the primer from lumping. Remove excess primer with dry, lint-free cotton cloths or pads attached to the polishing machine until the surface no longer appears wet. Leave the floor to dry for 3-4 hours. Between layers, buff the dry surface thoroughly using a maroon pad or a lacquer sanding pad and vacuum thoroughly. Apply WOCA Invisible Oil. Carefully follow the product instructions.

NoteTxt After 24 hours, we recommend that the surface is treated with Invisible Oil Care to improve the floor's resistance to stains and wear.

DryingTime

DryingTime Before treatment with Invisible Oil: 3-4 hours at 68°F

FullyHard 7 days at 68°F

Rec After 24 hours, the oiled surface must be treated with Invisible Oil Care to improve the floor's resistance to stains and wear.



Techdata_label

Density	1.00-1.10 g/ml
SolidContent	12 %
ShelfLife	24M
AppTemp	+15-30°C
Viscosity	Approx. 25
Consumption	86-129 sq. ft./L, depending on wood type and surface
Colours	Neutral
CleaningTools	Use warm water
Storage	+ 50-77°F. Store carefully. Keep out of reach of children. Must not be exposed to heat (e.g. sunlight). Store frost-free.
VOC Max	This product contains max. 10 g VOC/L. Permitted value is 500 g VOC/l (cat.A/i).
AvailPotSizes	2.5 L

MaintenanceProd

BasicOilingProd	Invisible Oil, #525010/525025
WeeklyCleanProd	Natural Soap White, #511110
MonthlyCareProd	Oil Refreshing Soap, #511210
MaintenanceHdn	Invisible Oil Care, #525510
RelatedProducts	Intensive Wood Cleaner, #551525

Contact_Label

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

Disclaimer_Long