



Master Color Oil provides color and protection in one product. The oil penetrates the wood and ensures a hardwearing surface with high resistance to water and dirt. It is perfect for indoor use on all unfinished, new or newly-sanded surfaces in all wood species.

- **Resistant to dirt and fluids, e.g. water, coffee, tea and red wine**
- **Available in many different colors**
- **Gives the wood a beautiful, breathable surface**
- **Indoor climate labelled**



AppArea

For untreated, new or newly-sanded wooden surfaces.

Work_Descrip_Label

Preparation_Label Product, room and floor temperature must be between 59-86°F. Wood humidity must not exceed 12%. Ensure good ventilation during application and when drying. The wood must be newly sanded, use grit 100-120 for the final sanding. Vacuum thoroughly. Clean the wood with WOCA Intensive Wood Cleaner and leave it to dry for at least 8 hours before applying the oil.

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment Thoroughly shake the container of Master Color Oil, both before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply the oil using a short-bristled paint roller (4-6 mm) in an even coat. Work in small areas of no more than 100 sq.ft. at a time. Leave the oil to soak in for 10-20 min. If the oil soaks quickly into the wood, apply more oil. Polish the oil into the wood until the surface appears saturated. Use a buffing machine with a red pad for large areas and a polishing cloth/pad manually for small areas. Remove excess oil with dry, lint-free cotton cloths or pads until the surface no longer appears wet. Continue until the whole area has been polished and excess oil has been thoroughly removed. To ensure a good saturation the surface should be re-polished with 3 fl.oz. Master Color Oil per 100 sq.ft. within 6-12 hours after the first application. The oil should be polished thoroughly, as described earlier.

DryingTime

DryingTime 12-24 hours at 68°F

FullyHard 7 days at 68°F



Techdata_label

Density	0.90-0.95 g/ml.
SolidContent	50-55%
ShelfLife	3 years
AppTemp	+59-77°F and approx. 50% air humidity.
Consumption	110-130 sq.ft./L
Colours	Natural, White, Brazil Brown, Castle Grey, Extra White, Walnut, Black, Rhode Island Brown, Antique, Extra Grey, Light Brown
CleaningTools	Use WOCA Solvent or turpentine
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	30 g/l.
AvailPotSizes	1, 2.5, 5

MaintenanceProd

WeeklyCleanProd	Natural Soap, #511010US
MonthlyCareProd	Oil Refreshing Soap, #511210US
ReOilingProduct	Maintenance Oil, #527310A/527410AA Maintenance Gel, #527802A/527902A
RelatedProducts	Intensive Wood Cleaner, #551525A

Contact_Label

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.