

Fastfiller is used for efficient and durable repairs of cracks and knotholes in wood prior to finishing. It bonds tightly to the wood, is easy to sand, cures fast and does not shrink or crack. The filler is powder-based and designed to accept stains, oils, wax and lacquers very fast and naturally, creating a uniform and natural look. Fastfiller is an environmentally friendly product based on pure natural raw materials, 90 % animal proteins and mineral components, and it must be mixed with water before use.

- **Quick-drying**
- **Easy to sand**
- **Does not shrink**
- **Must be treated afterwards with WOCA products**



Application area

For the repair of cracks, knotholes and other holes in all types of wood.

Work description

Treatment	0
Please note	Viscosity correction: A very small amount of water may be added to the mixture once or twice during the work process.

Drying time

Drying time	30-60 minutes at 20°C
-------------	-----------------------



Fastfiller

For manual filling of knotholes in wood

Technical Data Sheet

29.01.2022 - p. 2/2

Technical data

Density	2.40-2.60 g/ml.
pH-value	pH 7-8
Solid content	95-100%
Shelf life	3 years
Viscosity	35-40 Sec. DIN Cup 4
Colours	Smoked oak
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	0 g/L
Packaging	20 liters

Maintenance and related products

Weekly cleaning	Depends on the finishing oil
Monthly care	Depends on the finishing oil

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.