



Exterior Wood Oil is to be used outdoor for basic treatment and maintenance of new and previously oiled wood surfaces such as decks, garden furniture, cladding etc. The special water-based composition of oil components ensures that the product is water-dilutable and friendly to the environment. The oil enhances the natural color and grain of wood. Exterior Wood Oil Natural is recommended to enhance the natural color structure of the wood. For rejuvenating of old wood surfaces, the pigmented oils are ideal as they recreate the original color of the wood. A change of color of the deck is also possible by applying e.g. the grey, anthracite or black oil.

- **Provides a strong water and dirt-repellent surface**
- **Enhances the natural color and grain of the wood**
- **Fast-drying**
- **All varieties have UV protection**



AppArea

For basic treatment and maintenance of new and previously oiled wood surfaces outdoor such as decks, garden furniture, cladding etc. May be used on traditional wood species such as pine and larch and on exotic species such as teak, mahogany, and ipé.

Work_Descrip_Label

Preparation_Label Clean new wooden surfaces as well as old surfaces with WOCA Exterior Wood Cleaner before starting the oil treatment. Then leave the wood to dry for at least 24 hours so that the humidity is not above 17%. Sand down any rough wood fibres with sandpaper, grit 120. Make the application in dry weather only, min. temp. 55°F. Avoid direct sunlight and high temperatures.

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment Stir the oil thoroughly before use. Avoid direct sunlight and high temperatures. Apply an even and thin coat of oil with a brush or WOCA Oil Applicator. Treat the end grain wood first. The wet oil may have a white shade. When the water has evaporated after a few minutes, the wood will appear oiled. Wipe off any excess oil with clean cotton cloths after no more than 5 minutes. Take particular care of removing excess oil from joints and grooves. If the surface does not appear saturated with oil, repeat steps. When the wood is dry, it may be polished with a polishing pad or polishing machine to ensure an extra hard-wearing surface.

NoteTxt Non pressure-treated softwood must be primed with the WOCA Exterior Wood Primer.

Attention (for furniture): Please note that Exterior Wood Oil in the black, anthracite and walnut color are recommended to be finished with a coat of Exterior Wood Oil Natural to avoid excess color coming off.

DryingTime

FullyHard It takes 24 to 48 hours for the oil to harden thoroughly, depending on weather conditions and outdoor temperature. The wood must not be exposed to water during this period.



Techdata_label

Density	0.98-1.1
ShelfLife	36M
Viscosity	23-32 DIN CUP 4
Consumption	86 to 129 sq. ft./L depending on wood and its surface.
Colours	11 colours
CleaningTools	Clean tools with water
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOCTxt	This product contains a maximum of 20 g VOC/L. The limit value is 130 g VOC/L [cat. A/f].
AvailPotSizes	0.75 L - 2.5 L
Re-treatment	Repeat the oil treatment when required. Start cleaning the surface with WOCA Exterior Wood Cleaner.

MaintenanceProd

DeepCleanProd	Exterior Wood Cleaner
RelatedProducts	Exterior Wood Primer

Contact_Label

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

Disclaimer_Long