



Exterior Wood Primer

Water-based primer for highly absorbent wood

Technical Data Sheet

30.01.2022 - p. 1/2

Exterior Wood Primer is a water-based primer for priming surfaces such as façades, windows, fences and carports. The product protects the wood, as well as enhancing adhesion and durability of a subsequent surface treatment. Exterior Wood Primer is very well suited for fir, accoya, larch, pine, oak and pressure-impregnated wood.

- **Reduces cracking in the wood**
- **Extends the lifetime of the wood**
- **Protects the wood against moisture**



Application area

For new and old wood. Very well suited for fir, accoya, larch, pine, oak and pressure impregnated wood.

Work description

Preparation	<p>Clean the surface with WOCA Exterior Wood Cleaner. The surface must be completely dry and free of dust and dirt. New wood should be treated as soon as possible. Can also be used as a pre-treatment for previously oiled wood that has been weathered. The treatment with Exterior Wood Primer must be performed in dry weather, at a temperature between 15-30° C. Avoid direct sunlight and intense heat. Wood humidity must not exceed 17%.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Shake the container well. Apply Exterior Wood Primer undiluted, with a brush or roller. It is important that the product is applied thoroughly and evenly. Start with the end sections of the wood. Leave the wood to dry for at least 24 hours before treatment.</p>
Please note	<p>Exterior Wood Primer is a pre-treatment product, so the surface must then be treated with WOCA Exterior Wood Oil within 14 days. Make sure that you have properly sealed the container after use. Check the treated surfaces annually. Repair any damage immediately.</p>

Drying time

Drying time	24 hours at 20°C
Fully hard	24 hours at 20°C



Exterior Wood Primer

Water-based primer for highly absorbent wood

Technical Data Sheet

30.01.2022 - p. 2/2

Technical data

Density	1.00-1.10 g/ml.
Solid content	10-20%
Shelf life	2 years
Application Temperature	+15-25°C and approx. 50% air humidity.
Coverage	8-10 m ² /L
Colours	Natural
Mixing ratio	Ready to use. Do not dilute.
Cleaning of tools	Use warm water
Storage	+10-30°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	This product contains max. 15 g VOC/l. The permitted value is 30 g VOC/l [cat.A/g].
Packaging	2.5 liters

Maintenance and related products

Deep cleaning	Exterior Wood Cleaner, #617925
Related products	Exterior Wood Oil, #6179XX

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.