



Exterior Wood Primer

Water-based primer for highly absorbent wood

Technical_Data_Sheet_Label

02.03.2021 - p. 1/2

Exterior Wood Primer is a water-based primer for priming surfaces such as façades, windows, fences and carpports. The product protects the wood, as well as enhancing adhesion and durability of a subsequent surface treatment. Exterior Wood Primer is very well suited for fir, accoya, larch, pine, oak and pressure-treated wood.

- **Reduces cracking in the wood**
- **Extends the lifetime of the wood**
- **Protects the wood against moisture**



AppArea

For new and old wood. Very well suited for fir, accoya, larch, pine, oak and pressure impregnated wood.

Work_Descrip_Label

Preparation_Label The treatment with Exterior Wood Primer must be performed in dry weather, at a temperature between 59-86°F. Avoid direct sunlight and intense heat. Wood moisture content must not exceed 17%. Clean the surface with WOCA Exterior Wood Cleaner. The surface must be completely dry and free of dust and dirt. New wood should be treated as soon as possible. On previously-treated wooden surfaces, remove old loose paint and oil.

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment Shake the container well. Apply Exterior Wood Primer undiluted, with a brush or roller. It is important that the product is applied thoroughly and evenly. Start with the end sections of the wood.

NoteTxt Exterior Wood Primer is a pre-treatment product, so the surface must then be treated with WOCA Exterior Wood Oil or paint within 14 days. Make sure that you have properly sealed the container after use. Check the treated surfaces annually. Repair any damage immediately.

DryingTime

DryingTime 24 hours at 68°F.



Exterior Wood Primer

Water-based primer for highly absorbent wood

Technical_Data_Sheet_Label

02.03.2021 - p. 2/2

Techdata_label

Declaration	Drying oils.
ShelfLife	24M
AppTemp	+59-86°F.
Consumption	85-110 sq.ft./L.
CleaningTools	Clean in warm water.
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer (max. +77°F).
VOCTxt	VOC-Max: 15 g/l.
AvailPotSizes	84.54 fl.oz.

MaintenanceProd

RelatedProducts	Exterior Wood Cleaner. Exterior Wood Oil.
ApplicationTool	Roller or brush.

Contact_Label

WOCA Denmark A/S
Tværevej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

Disclaimer_Long