



Exterior Wood Primer

**Water-based primer for highly absorbent wood**

Technical\_Data\_Sheet\_Label

29.01.2022 - p. 1/2

Exterior Wood Primer is a water-based primer for priming surfaces such as façades, windows, fences and carports. The product protects the wood, as well as enhancing adhesion and durability of a subsequent surface treatment. Exterior Wood Primer is very well suited for fir, accoya, larch, pine, oak and pressure-treated wood.

- **Reduces cracking in the wood**
- **Extends the lifetime of the wood**
- **Protects the wood against moisture**



## AppArea

For new and old wood. Very well suited for fir, accoya, larch, pine, oak and pressure impregnated wood.

## Work\_Descrip\_Label

**Preparation\_Label** The treatment with Exterior Wood Primer must be performed in dry weather, at a temperature between 59-86°F. Avoid direct sunlight and intense heat. Wood moisture content must not exceed 17%. Clean the surface with WOCA Exterior Wood Cleaner. The surface must be completely dry and free of dust and dirt. New wood should be treated as soon as possible. On previously-treated wooden surfaces, remove old loose paint and oil.

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

**Treatment** Shake the container well. Apply Exterior Wood Primer undiluted, with a brush or roller. It is important that the product is applied thoroughly and evenly. Start with the end sections of the wood.

**NoteTxt** Exterior Wood Primer is a pre-treatment product, so the surface must then be treated with WOCA Exterior Wood Oil or paint within 14 days. Make sure that you have properly sealed the container after use. Check the treated surfaces annually. Repair any damage immediately.

## DryingTime

**DryingTime** 24 hours at 68°F



Exterior Wood Primer

**Water-based primer for highly absorbent wood**

Technical\_Data\_Sheet\_Label

29.01.2022 - p. 2/2

## Techdata\_label

Declaration	Drying oils.
ShelfLife	2 years
AppTemp	+59-77°F and approx. 50% air humidity.
Consumption	85-110 sq.ft./L
Colours	Natural
CleaningTools	Use warm water
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	VOC-Max: 15 g/l.
AvailPotSizes	2.5

## MaintenanceProd

RelatedProducts	Exterior Wood Cleaner. Exterior Wood Oil.
-----------------	--

## Contact\_Label

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
[info@wocadenmark.com](mailto:info@wocadenmark.com)  
[wocadenmark.com](http://wocadenmark.com)

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*