

If left untreated, outdoor wood takes on a beautiful grey patina. You can now maintain this look, while at the same time giving the wood long-lasting protection and extend its lifetime. The solution is Exterior Wood Shield, which is ideal for the treatment of untreated outdoor wooden surfaces, such as wooden garden furniture and patios. Exterior Wood Shield produces a water- and grime-resistant surface, while retaining the patina of the wood, as it does not add colour to it.

- Gives the wood a water and dirt-resistant surface
- Extends the lifetime of the wood
- Increases the resistance of wood to wind and weather
- Can also be used in other absorbent outdoor surfaces such as tiles, concrete and stone



## Application area

---

For all types of outdoor, untreated wood surfaces, composites and stone.

## Work description

---

Preparation	<p>The surface must be completely dry and free of dust, dirt and algae. If the surface is very grimy, clean first with WOCA Exterior Wood Cleaner. For optimum protection, we recommend light sanding of the surface afterwards, so the wood is completely smooth and pleasant to walk on.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Shake the container well. Apply Exterior Wood Shield using a WOCA Oil Applicator, spraygun, brush or by dipping the wood. It is important that the product is applied thoroughly and evenly. For application using a spraygun, hold the spray nozzle approx. 10-15 cm from the surface. Leave the wood to dry.</p>
Note	<p>Surfaces treated with Exterior Wood Shield cannot be painted or oiled and should therefore be sanded down and cleaned with WOCA Exterior Deep Cleaner before treating the wood WOCA Exterior Wood Oil.</p>

## Drying time

---

Fully hard	Exterior Wood Shield does not give full protection until 2-4 days have passed.
------------	--



## Technical data

---

Density	1.00 g/ml
Shelf life	24M
Application Temperature	+ 15-30°C
Coverage	20-30 m <sup>2</sup> /L depending on how absorbent the surface is
Mixing ratio	Undiluted
Storage	+10-25°C. Keep out of reach of children. Must not be exposed to heat (e.g. sunlight). Store frost-free.
VOC	This product contains max. 30 g VOC/l. The permitted value is 140 g VOC/l (cat.A/i).
Packaging	2.5 L
Re-treatment	1-2 times a year

## Maintenance and related products

---

Deep cleaning	Exterior Wood Cleaner, #617925 Exterior Deep Cleaner, #607542
Related products	Exterior Wood Oil, #6079xx
Application tools	Patio scrubber, #599601 Telescopic rod, #599651

## Contact

---

WOCA Denmark A/S  
Tværvvej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.