

If left untreated, outdoor wood takes on a beautiful grey patina. You can now maintain this look, while at the same time giving the wood long-lasting protection and extend its lifetime. The solution is Exterior Wood Shield, which is ideal for the treatment of untreated outdoor wooden surfaces, such as wooden garden furniture and patios. Exterior Wood Shield produces a water- and grime-resistant surface, while retaining the patina of the wood, as it does not add colour to it.

- **Gives the wood a water and dirt-resistant surface**
- **Extends the lifetime of the wood**
- **Increases the resistance of wood to wind and weather**
- **Can also be used in other absorbent outdoor surfaces such as tiles, concrete and stone**



## Application area

---

For all types of outdoor, untreated wood surfaces, composites and stone.

## Work description

---

Preparation	<p>The surface must be completely dry and free of dust, dirt and algae. If the surface is very grimy, clean first with WOCA Exterior Wood Cleaner. For optimum protection, we recommend light sanding of the surface afterwards, so the wood is completely smooth and pleasant to walk on.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Shake the container well. Apply Exterior Wood Shield using a WOCA Oil Applicator, spraygun, brush or by dipping the wood. It is important that the product is applied thoroughly and evenly. For application using a spraygun, hold the spray nozzle approx. 10-15 cm from the surface. Leave the wood to dry.</p>
Please note	<p>Surfaces treated with Exterior Wood Shield cannot be painted or oiled and should therefore be sanded down and cleaned with WOCA Exterior Deep Cleaner before treating the wood WOCA Exterior Wood Oil.</p>

## Drying time

---

Fully hard	3 days at 20°C
------------	----------------



## Technical data

---

Density	1.00-1.10 g/ml.
Shelf life	2 years
Application Temperature	+15-25°C and approx. 50% air humidity.
Coverage	20-30 m <sup>2</sup> /L
Colours	Colourless
Mixing ratio	Ready to use. Do not dilute.
Storage	+10-30°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	This product contains max. 30 g VOC/l. The permitted value is 140 g VOC/l (cat.A/i).
Packaging	2.5 liters
Re-treatment	1-2 times a year or when required.

## Maintenance and related products

---

Deep cleaning	Exterior Wood Cleaner, #617925 Exterior Deep Cleaner, #607542
Related products	Exterior Wood Oil, #6079xx

## Contact

---

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*