



Industrial Oil 1502

**Basic industrial oxidizing oil for wooden floors**

Technical Data Sheet

29.01.2022 - p. 1/2

Industrial Oil 1502 is a fast air-drying wood finish based on natural vegetable oils with high penetration, ensuring a durable wood floor combined with an effective and flexible application process.

- **Fast air-drying oil**
- **Easy handling in the production**



## Application area

For treatment of wooden floors, parquets, wall panels and ceiling panels in hardwood and softwood.

## Work description

Please note      Viscosity correction: Correction can be made with WOCA Solvent only, #328575I.

## Drying time

Drying time      Drying on racks or pallets. Drying is accelerated in drying tunnel with max. 40°C and good air circulation.

Fully hard      7 days at 20°C



Industrial Oil 1502

**Basic industrial oxidizing oil for wooden floors**

Technical Data Sheet

29.01.2022 - p. 2/2

## Technical data

Density	0.90-0.95 g/ml.
Solid content	40-50%
Shelf life	3 years
Viscosity	20-25 Sec. DIN Cup 4
Coverage	25-40 m <sup>2</sup> /L
Colours	Natural
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	515 g/L
Packaging	20 liters

## Maintenance and related products

Weekly cleaning	WOCA Natural Soap
Monthly care	WOCA Oil Refreshing Soap
Related products	Re-oiling: WOCA Maintenance Oil WOCA Maintenance Oil Diamond Active

## Contact

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
[info@wocadenmark.com](mailto:info@wocadenmark.com)  
[wocadenmark.com](http://wocadenmark.com)

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*