

High Solid Master Oil is used for oil finishing of wood floors with floor machine. The oil ensures a hard-wearing, dirt and water repellent surface. High Solid Master Oil is ideal for basic finishing of unfinished, new and newly sanded interior woodwork. It is suitable for any type of wood floor including cork. Use floor machine for the polishing.

- Suitable for all types of wood floors
- Especially suitable for commercial areas
- To be applied solely by machine
- High solid content
- Certified by IBR



## Application area

---

High Solid Master Oil Natural enhances the natural colour of the wood, whereas High Solid Master Oil White preserves the wood's own colour almost as unfinished without enhancing it. By this choice the colour intensity of the wood surface may be systematically controlled and be adapted to the ambience. Typically, lye treated surfaces are being white oiled.

## Work description

---

**Preparation** The unfinished woodwork should be freshly sanded with grit 100-120. Clean the floor with 125 ml Wood Cleaner mixed into 5 litre water. The floor must be completely dry and free from dirt and grease before the oil application. Recommended moisture max. 12%. The oiling is made at min. 18°C (64°F). Product, room and floor temperature should be between 15°C–35°C. Ensure good ventilation at all times during the application and drying time.

## Drying time

---

**Recommendation** Clean tools with Solvent.

## Technical data

---

Declaration	Vegetable oil components, isoparaffin, pigments (white). Contains Cobalt bis (2-ethylhexanoate). May produce an allergic reaction.
Density	0,9-1,1
Shelf life	36M
Coverage	18-20 m <sup>2</sup> /litre
Colours	Natural, white and extra white.
Cleaning of tools	With Solvent.
Storage	Store safely, out of reach of children Do not expose to heat (e.g. sunlight). Store frost-free.
VOC	This product contains a maximum of 35 g VOC/L. The limit value is 500 g VOC/L (cat. A/i).
Packaging	2.5 litre and 5 litre

## Maintenance and related products

---

Application tools	A polishing machine with beige polishing pad. Paint roller and cotton cloths.
-------------------	---

## Contact

---

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.