



Maintenance Oil may be used for the maintenance of all oxidative oiled wood surfaces and is especially suitable for the regular maintenance of oiled wood floors. Can be applied manually with a polishing pad and by machine (floors larger than 8-10 m²).

- **Makes floors even more durable**
- **Highlights the glow and grain structure of the wood**
- **Gives the wood a beautiful, breathable surface**
- **IBR-certified**



Application area

For care and maintenance of all oxidative oiled wood surfaces, especially floors.

Work description

Preparation	<p>Product, room and floor temperature should be between 15–35°C. Ensure good ventilation at all times during the application and drying time. Clean the floor with WOCA Intensive Wood Cleaner. Leave the floor to dry for at least 8 hours. The floor must be completely dry.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Shake the container carefully. Apply approx. 1 dl oil per 4 m² with pad, short-haired paint roller, cotton cloth or use polishing machine for large surfaces. It is important that the Maintenance Oil is carefully polished into the wood. Continue polishing until the wood appears saturated and the surface looks uniform. Wipe the floor with clean, dry cotton cloths before proceeding with the next section of floor to be finished. The floor should not appear wet and there should not be any excess oil left on the surface after polishing. Continue stepwise till the floor has been finished.</p>
Please note	<p>Do not clean the floor or expose it to water during the first 48 hours, while the oil is curing.</p>

Drying time

Drying time when machine polished	3-4 hours at 20°C
Drying time when hand polished	24-48 hours at 20°C
Fully hard	24-48 hours at 20°C



Technical data

Declaration	Vegetable oil components, isoparaffin, pigments.
Density	0.85-0.90 g/ml.
Solid content	50-55%
Shelf life	3 years
Application Temperature	+15-25°C and approx. 50% air humidity.
Coverage	30-40 m ² /L
Colours	Natural, White, Grey, Brown, Extra White
Cleaning of tools	Use WOCA Solvent or turpentine
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	This product contains a maximum of 490 g VOC/L. The limit value is 700 g VOC/L (cat. A/f (OB)).
Packaging	1 liter, 2.5 liters

Maintenance and related products

Weekly cleaning	Natural Soap, #511010
Monthly care	Oil Refreshing Soap, #511210
Re-oiling	Master Colour Oil, #522055
Related products	Intensive Wood Cleaner, #551510A

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.