

Neutral Oil Industry is an environmentally friendly product based on vegetable oils, water and drying agents. It is used for new or newly sanded wood and creates a neutral finish that resembles untreated wood. The oil offers a good protection of the surface while maintaining the raw wood look.

- **Fast air-drying oil**
- **Manual application**
- **Easy application on a variety of processes**
- **Generates well-tested durable wooden surfaces**



Application area

For surface treatment of wooden surfaces in solid wood, hardwood and softwood.

Work description

Please note Viscosity correction: Correction can be made with a maximum of 5 % water.

Drying time

Drying time Drying on racks or pallets. Drying is accelerated in drying tunnel with max. 40°C and good air circulation.

Fully hard 7 days at 20°C



Neutral Oil Industry air-dry [manual appl.]

Fast-drying industrial oxidizing oil for wooden surfaces

Technical Data Sheet

29.01.2022 - p. 2/2

Technical data

Density	1.00-1.10 g/ml.
Solid content	20-30%
Shelf life	2 years
Viscosity	20-25 Sec. DIN Cup 4
Coverage	20-40 m ² /L
Colours	Available in selected colours.
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	75 g/L
Packaging	20 L metal pails.

Maintenance and related products

Weekly cleaning	WOCA Natural Soap
Monthly care	WOCA Oil Refreshing Soap
Related products	Re-oiling: WOCA Invisible Oil Care

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.