



Master TS-2K Lacquer is a two-component water-based floor lacquer approved for sports areas and multi-purpose halls according to the European DS/EN 14904. It offers a strong protection, excellent durability and an incredibly high resistance to heel marks, abrasion and scratches. Master TS-2K Lacquer is also indoor climate labelled, DIBt-approved, approved according to DIN 51130: R9 and fire tested according to EN 12501-1: 2018: Bf11-S1. Master TS-2K Lacquer is used in combination with WOCA Line Marking which is available in 6 different colours:RAL 1021 YellowRAL 3000 RedRAL 5010 BlueRAL 6029 GreenRAL 9016 White



Application area

Wooden floors in Indoor sports areas and multi-purpose halls

Work description

Preparation

It is important that both wood and lacquer have a temperature of min. 15°C, but preferably around 20°C, and a humidity of approx. 50 %. The relative humidity must not vary more than 30 % during the year. Provide good ventilation in the room for drying time and evaporation. Master TS-2K Lacquer adheres to most surfaces with the right preparation and drying time. Always remember to do a test run at a less visible place to check the compatibility of the wood and Master TS-2K Lacquer. Scratch with a coin to check the adhesion. Alternatively, try WOCA Master Multi Primer for exotic wood species or old wood previously treated with oil or wax.

Drying time



Technical data

Density	0.95-1.00 g/ml.
Shelf life	1 year
Coverage	6-10 m ² /L
Colours	Yellow, Blue, Green, White, Black, Red
Mixing ratio	10% or 500 ml to 5 L lacquer
Cleaning of tools	Use soap and water
Packaging	2.25 liters

Maintenance and related products

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.