

Softwood Lye is used for priming of unfinished or newly sanded interior woodwork such as floors, stairs, furniture, and panels. The priming minimizes the wood from yellowing and enhances the natural grain of the wood, producing a white wash finish. Softwood Lye may be used for all types of softwood such as pine, spruce, and pitch-pine. Used on larch wood, an antique grey/brownish finish is created. Softwood Lye may not be used on hardwood. The final color is achieved after 1-2 months.



Application area

Work description

Preparation Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Note Softwood Lye can assume a greenish colour which will disappear in the course of time.

Drying time



Technical data

Shelf life	24M
Coverage	10-12 m ² /L, depending on wood type and surface.
Storage	+10-25°C. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Maintenance and related products

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.